



AMAZING RESULTS

- · Integral transformation of the calorific value of the gas into radiant energy
- Medium wave infrared emission (3 8 microns for optimal performance)
- · Large irradiation surface thanks to the use of 12 radiant panels
- Environmentally friendy Gas Catalytic panels do not produce Carbon Monoxide (CO) nor Nitrogen Oxides (NOx), moreover they abate VOC's (Volatile Organic Compounds) with consequent reduction of toxic global emissions
- · Maximum safety guaranteed by explosion-proof panels with absolute absence of flames
- · Operation with natural gas or LPG

BENEFITS

- · No risk in use on plastic and aluminium parts
- · Simplicity of use and programming through touch screen
- · Possibility to change the speed in real time
- · It can be retrofitted in existing or new spray booths
- Up to 3 different drying recipes in a single session
- Custom formulation for any brand of water-based and solvent-based paint products
- Assistance reduced to a minimum thanks to remote control and system simplicity and reliability
- Productivity can be doubled with rapid return on investment

ENERGY SAVING

- Drying time is reduced by up to 70%
- Very low electricity consumption due to short use (only in the preheating phase)
- Fuel consumption (methane or LPG) reduced by up to 80%

Technical data E6

Gas Type		CH4 GPL	CH4 GPL
Minimal gas pressure	mbar	20 60	20 60
Indicative gas consumption		4,7 m3/h 3,7 kg/h	4,7 m3/h 3,7 kg/h
Minimal air pressure	bar	1	1
Indicative air pressure	m³/h	0,4	0,4
Electrical power supply	kW	8	8
Voltage	V	400	400
Current	Α	13	13
Frequency	Hz	50÷60	50÷60
Phases	N°	3+N	3+N
Catalytic panels	N°	12	12
Radiant surface	m²	2,4	2,4
Weight without rails	kg	400	400
Dimensions	m	3x2,2x0,8	3x2,4x0,8

E6PLUS













Greentech Dryers Srl

Head office and production site Via Colpi, 33 - I 35010 LIMENA (PD) VAT IT03896150244 Phone +39 049 8843244 Web www.greentechdryers.com Email info@greentechdryers.com