





AMAZING RESULTS

- · Integral transformation of the calorific value of the gas into radiant energy
- Medium wave infrared emission (3 8 microns for optimal performance)
- · Large irradiation surface thanks to the use of 3/4 large-area radiant panels
- Environmentally friendly Gas Catalytic panels do not produce Carbon Monoxide (CO) nor Nitrogen Oxides (NOx), moreover they abate VOC's (Volatile Organic Compounds) with consequent reduction of toxic global emissions
- · Maximum safety guaranteed by explosion-proof panels with absolute absence of flames
- · Operation with natural gas or LPG

BENEFITS

- · No risk in use on plastic and aluminium parts
- · Simplicity of use and programming through touch screen
- · Possibility to change the speed in real time
- · Installation for up to 5 preparation areas
- · Custom formulation for any brand of water-based and solvent-based paint products
- · Assistance reduced to a minimum thanks to remote control and system reliability
- · Productivity can be doubled with rapid return on investment

ENERGY SAVING

- Drying time is reduced by up to 70%
- Very low electricity consumption due to short use (only in the preheating phase)
- Fuel consumption (methane or LPG) reduced by up to 80%

Technical data

E7

E7PLUS

Gas Type		CH4 GPL	CH4 GPL
Minimal gas pressure	mbar	20 60	20 60
Indicative gas consumption		1,2 m3/h 0,9 kg/h	1,6 m3/h 1,2 kg/h
Minimal air pressure	bar	1	1
Indicative air pressure	m³/h	0,2	0,2
Electrical power supply	kW	5	6
Voltage	V	400	400
Current	Α	8	10
Frequency	Hz	50÷60	50÷60
Phases	N°	3+N	3+N
Catalytic panels	N°	3	4
Radiant surface	m²	0,6	0,8
Weight without rails	kg	150	150
Dimensions	m	2,8x1x0,5	2,8x1x0,5







 ϵ









Greentech Dryers Srl

Head office and production site
Via Colpi, 33 - I 35010 LIMENA (PD)

VAT IT03896150244

Phone +39 049 8843244

Web www.greentechdryers.com
Email info@greentechdryers.com